



NF98-QM57-LF



1. Intel® QM57 Express Chipset
2. Supports Intel Core™ i3, i5, i7 Mobile Processors
3. Dual Channel DDR3-800/1066 up to 8GB
4. Intel 82577LM Gigabit LAN
5. Intel Active Management Technology (iAMT 6.0)
6. PCI Express x16 2.0 Slot, PCI Express Mini Card Slot
7. Integrated 24-bit Dual Channel LVDS
8. 5-port SATA 3Gb/s with RAID 0, 1, 5, 10 & JBOD Support
9. HDMI, DVI-D, and VGA Video Outputs
10. Built-in Watchdog Timer Technology
11. Mini-ITX Form Factor (170mm x 170mm)
12. Includes CPU Heatsink/Fan for <35W Processors










Board Specifications

■ CPU	<ul style="list-style-type: none"> Intel Core i3, i5, i7 mobile processors Socket G (rPGA988A), Includes CPU Heatsink/fan for <35W processors
■ Chipset / Video	<ul style="list-style-type: none"> Intel QM57 Express Chipset Intel HD Graphics (requires compatible CPU with built-in GPU)
■ Memory	<ul style="list-style-type: none"> 2 * SODIMMs Sockets for un-buffered dual channel DDR3-800/1066 up to 8 GB
■ Expansion Slots	<ul style="list-style-type: none"> 1 * PCI Express x16 2.0 (by 16-lane) slot 1 * PCI Express Mini Card slot
■ Storage	<ul style="list-style-type: none"> 5 * Serial ATA II 3Gb/s connectors
■ Audio	<ul style="list-style-type: none"> VIA VT 1705 6-Channel HD Audio
■ Networking	<ul style="list-style-type: none"> Intel 82577LM Gigabit Ethernet LAN Intel Active Management Technology support (iAMT 6.0)
■ LVDS	<ul style="list-style-type: none"> Onboard 24-bit dual channel LVDS connector
■ USB	<ul style="list-style-type: none"> Embedded 10 * USB 2.0/1.1
■ Special Features	<ul style="list-style-type: none"> Supports ACPI S3, CPU Smart FAN, All solid capacitors Watchdog hardware monitor
■ Rear I / O	<ul style="list-style-type: none"> 6 * USB 2.0/1.1 ports 1 * PS/2 KB/mouse combo connector 1 * RJ-45 port 1 * HDMI port 1 * VGA port 1 * DVI-D port 1 * eSATA port 1 * Audio port (Line-in, MIC and Line-out) 1 * Coaxial Out & 1 * Optical Out
■ Internal I / O	<ul style="list-style-type: none"> 2 * USB 2.0/1.1 headers for 4 USB ports 1 * 24-bit dual channel LVDS header 1 * Serial header (RS232/422/485) 1 * GPIO header 1 * Audio header, 1 * Front panel header 1 * 24-pin ATX power connector, 1 * 4-pin 12V ATX power connector
■ BIOS	<ul style="list-style-type: none"> AMI EFI 64MB SMT Flash ROM
■ Form Factor	<ul style="list-style-type: none"> Mini-ITX Form Factor (170mm x 170mm)
■ Functional	<ul style="list-style-type: none"> ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
■ Compliance	<ul style="list-style-type: none"> CE, FCC, RoHS, EuP
■ Temperature	<ul style="list-style-type: none"> Operating within 0~60 centigrade Storage within -20-85 centigrade

*For more information visit our website <http://www.jetway.com.tw>

Product Accessories

 <p>Manual</p>	 <p>CD</p>	 <p>IO Shield</p>	 <p>COM Cable</p>	 <p>SATA Cable</p>	 <p>Thermal Grease</p>	 <p>CPU Fan</p>
---	---	--	--	--	---	--